



EU78WTT

Series with fixed frame section and 78 mm leaf section, and panel doors, mm 98. Glass area 50 mm. Beaten wood 20 mm, coupling Aluminum-Wood with PVC plugs. Air-water tightness open joint with central gasket EPDM.



PROFILES	- Fixed frame: 78 mm. - Door sections: 98 mm.	
CONSTRUCTION FEATURES	Windows to a door, windows in two or more wings to flap doors, balconies to a door, balconies with two doors, entry doors.	
GLASS/ES AND CLADDING	The profiles provide for the incorporation of low emissivity glass having a thickness of from 32 to 46 mm.	
FLAP DOOR CAPACITY	120 kg	
THERMAL TRANSMITTANCE	Tests performed in the laboratory with equipment in hot box with the procedures described in the UNI EN ISO 12412-2 Uf = 1,55 w/m²k	
TECHNICAL DATA		
PERMEABILITY TO AIR <i>EN-1026</i>	I	2 3 4
WATER RESISTANCE <i>EN-1027</i>	1A 2A 3A 4A 5A 6A 7A 8A 9A	
WIND RESISTANCE <i>Pressure test EN-12211</i>	I 2 3 4 5	
WIND RESISTANCE <i>Deflection</i>	A B C	

